



MILAN

MilanFix Smooth Surface Primer



DESCRIPTION

MilanFix Smooth is one component, synthetic resin based primer used as an adhesion promoter for lime and cement based coatings and especially plaster applications on smooth surfaces like fair faced concrete, wall and ceiling.

CLEANING

Clean all the tools with water immediately after use. Hardened materials can be removed mechanically only.

STORAGE

Store under cover, out of direct sunlight and protect from extreme temperatures. In tropical climates the product must be stored in air-conditioned environment.

SHELF LIFE

Shelf life is up to 12 months when stored as per recommendations.

PACKAGING

MilanFix Smooth is available in: **5 KG/ 12 KG.**



+964 7826668176

www.milan-iq.com

Baghdad - Aweij-Industrial Zone

USES

Multi-purpose, ready-to-use primer for internal and external floors and walls. Iso primer may be used to improve the bond of all types of cement, gypsum and lime-based plasters on substrates made from concrete, brickwork, vibro-compressed concrete blocks, light weight blocks and gypsum. Iso primer is also suitable for improving the bond of adhesives for ceramics, smoothing and levelling compounds on non-absorbent surfaces, such as ceramic, terrazzo and natural stone floors. Some application examples:

- Application of render on concrete, brick work, substrates, etc.
- Application of smoothing and levelling compounds on old ceramic, terrazzo and natural stone floors.
- Laying ceramic and natural stone floors directly on top of old ceramic floors.

COVERAGE

Consumption varies between **0.20** and **0.30 kg/m²** accc absorption of the substrate.

APPLICATION PROCEDURE

- Preparation of the substrate ,substrates must be clean well-cured and free from oil, grease, cement laitance.
- Removed easily from floors, walls and tools with water it must be removed with alcohol.

RECOMMENDATIONS:

- Apply at temperatures between **+5°C** and **30%**.
- Do not use ISO PRIMER **1054** in the presence of rising damp or rising humidity, and on continuously immersed surfaces.
- MilanFix Smooth is ready-to-use, don't add any thinning agent.
- Do not use as adhesion promoter for adhesives and le compounds on screeds and power-trowelled concrete.

HEALTH AND SAFETY

As with all construction chemical product, caution should be always be exercised. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting, but call for medical assistance immediately.

